2027 WOODY'S STREET STOCK RULES

TIRES/ RIMS – Hoosier 790 will be the only tire allowed. 6 tires will be allowed to be purchased on opening day for inventory. Then 1 tire per weekly points race and 2 tires per bigger event (does not include standard weekly races). All tires must be purchased at Star Speedway. NO chemical treating. All tires must meet 52 durometer. Questionable tires will have samples sent to Blue Ridge Labs. Those found to not conform will get 2 race suspensions, loss of points, $250 fine and be responsible for any costs incurred to Blue Ridge Labs. Rims may be 7" or 8".

TIRE REPLACEMENT- Damaged tire must have been bought on same day to claim! Flat tire replacement requests must be made at the event it occurs. Damaged tire must be handed in and a slip will be given to the competitor at the race of lost tire. The replacement tire must be purchased at the next scheduled Woody's Street Stock race.

***PLEASE READ RACE DAY PROCEDURES AS THEY WILL BE HIGHLY ENFORCED.**

- **TREAD WIDTH:** MAXIMUM 73" MEASURED FROM OUTSIDE TO OUTSIDE OF WHEEL BEAD .
- **RIDE HEIGHT:** 5" MINIMUM CHASSIS HEIGHT W/DRIVER IN CAR.
- **SPOILER:** 5" X 60" WITH A MAX HEIGHT OF 44" MEASURED FROM THE GROUND. NO SIDE SPOILERS.
- **CLUTCH:** ONLY STOCK APPEARING 10-½" FLYWHEEL & PRESSURE PLATE, NO MULTI DISC. NO ALUMINUM COMPONENTS ALLOWED.
- **LEFT SIDE WEIGHT:** 55.0 % MAXIMUM WITH DRIVER AFTER THE RACE.
- **SHOCKS/STRUTS/COIL-OVERS** $150.00 MAXIMUM M.S.R.P. COST. ALL SHOCKS MUST HAVE PART #'S ON THEM TO VERIFY THE COST. BILSTEIN SZ SERIES ARE ALLOWED. NO SCHRADER VALVES ALLOWED. GEN 3 AND GEN 4 STRUTS OR COIL-OVERS MAXIMUM M.S.R.P. IS $180.00 EXAMPLE KYB AGX ADJUSTABLE. NO BUMP SPRINGS OR BUMP STOPS ALLOWED.
- **BODIES:** STREET STOCK TYPE ONLY NO COMPLETE LATE MODEL ABC BODIES. NO OUTLAW WEDGE STYLE. REAR OF CAR MUST BE ENCLOSED WITH ALUMINUM. (JUST ABC ROOF IS ALLOWED) NO SIDE WINDOWS ALLOWED MAXIMUM 15" VENT WINDOW IS ALLOWED. MAXIMUM 1" ROOF/REAR WINDOW RAILS ALLOWED.
- **BUILT ENGINE:** ONLY SMALL BLOCK CHEVY, DODGE. AND FORD ALLOWED. ONLY CAST IRON HEADS AND BLOCKS ALLOWED. NO ALUMINUM!
- ONLY INTAKES ALLOWED ARE EDELBROCK CHEVY 2101 & 2116. FORD 2121 & 2181. DODGE 2176.
- **CRATE ENGINE:** ALL CRATE ENGINES MUST BE SEALED AND MATCH FACTORY SPECS INCLUDING HARMONIC BALANCER, ROCKER ARMS, VALVE SPRINGS, AND STOCK OIL PAN.
- **WEIGHT RULES:** ALL WEIGHTS ARE AFTER THE HEAT AND FEATURE. BUILT ENGINE WITH STOCK UNALTERED HOLLEY 4412 2 BARREL 500 CFM CARB 3000 LBS. NHMS 3050. 602 CRATE ENGINE WITH STOCK UNALTERED HOLLEY 650 4 BARREL CARB 2900 LBS. PART # 80541-1 OR -2 OR -3. ALL CARBURETORS MUST PASS GO-NO GO TOOLS. MUST HAVE CHOKE HORN. NO XP CARBS.
- **CAMSHAFT:** .460 MAXIMUM LIFT MEASURED AT THE VALVE.
- **HEADERS:** ONLY DOWN UNDER STREET STOCK TYPE HEADERS ALLOWED NO 180 UP AND OVER OF ANY KIND ALLOWED. MUST RUN TRACK APPROVED MUFFLERS.
- **IGNITION:** STOCK STYLE HEI ONLY NO MSD BOXES. MSD SOFT TOUCH REV LIMITERS ALLOWED.
- NO TRACTION CONTROL ALLOWED OF ANY KIND.
- **CHASSIS:** PERIMETER STYLE NO STRAIGHT RAIL. CAMARO CLIP CARS MUST HAVE LEAF SPRINGS. NO UNDERSLUNG LATE MODEL STYLE REAR CLIPS. THE REAR CHASSIS MUST GO OVER THE REAR END. MUST HAVE STOCK TYPE SPRINGS FOR MAKE AND MODEL. THE ONLY FABRICATED CLIPS ALLOWED WILL BE HAMM, JOHNSON, AND LEFTHANDER PART # 001358207. ONLY STOCK MOUNT STEERING BOXES ALLOWED NO RACKS UNLESS STOCK FROM FACTORY EXAMPLE 4th GEN CAMARO. ONLY STOCK SPINDLES ALLOWED. STOCK LOWER CONTROL ARMS OR HAMM AND JOHNSON STOCK REPLACEMENT ARE ALLOWED. 3-LINK REARS ALLOWED ONLY ON METRIC CARS UPPER LINK CAN HAVE RUBBER BISCUITS NO SPRINGS ALLOWED. NO 3 LINKS ON GEN 2 CAMAROS WITH LEAF SPRINGS. 3RD AND 4TH GEN TORQUE ARMS ARE ALLOWED. QUICK CHANGE REAR ENDS ALLOWED BUT ONLY WITH 5X5 HUBS.
- **WHEELBASE:** GEN 2 CAMARO AND METRIC 108" +/- 1". GEN 3 & 4 CAMAROS 101" +/- 1".
- CHALLENGER 110" +/- 1". CHEVELLE 112" +/- 1" AND MUST BE COIL SPRINGS WITH 3 OR 4 LINK.
- **SWAYBARS:** STOCK TYPE MUST BE MOUNTED ON TOP OF A-FRAME. NO 3pc BARS ALLOWED. AFTERMARKET SWAY BARS UNDER LOWER A-FRAME MUST ADD 50LBS.
- **RADIOS:** NO RADIOS ALLOWED EXCEPT THOMPSON AND NHMS. SPOT MIRRORS ARE ALLOWED.
- **TRANSPONDERS:** MUST BE MOUNTED 12" BACK FROM CENTER OF THE REAR END AXLE TUBE.
- **FUEL:** SUNOCO STANDARD 110/GTX 98 OR PUMP GAS 87-93 OCTANE. NO FUEL ADDITIVES ALLOWED.
- **GEAR RULES:** THOMPSON 4.71 MAXIMUM FINAL DRIVE GEAR RATIO.