



(UPDATED 5-5-26)

2026 Pro-V8 Rules

GENERAL RULES

1. All cars must have a transponder and receiver on and working at all times car is on the speedway including practice. Failure to do so will result in a black flag in practice and not being scored in race events. No points or payouts will be given.
2. All drivers must have a valid 2026 Star License and car registration to receive points or payouts.
3. All cars must have numbers on roof, both doors, and upper corner of windshield. Roof and door numbers must be a minimum of 18" in contrasting color.

SAFETY

1. Must have aluminum Race Seat that is bolted to brackets and firmly welded to roll bar assembly. All bars within driver's reach must be padded with approved roll bar padding.
2. Minimum 4 point roll cage
3. SFI 5 point racing harness must be less than 5 years old from manufacture date
4. Snell 2010 rated full face helmets only. Highly recommended the use of Snell SA2010 or newer
5. Window net is required
6. SFI Fire Suit in good condition- must be free from holes, grease, etc
7. SFI Racing Gloves in good condition required
8. SFI Racing Shoes in good condition are required
9. Head and Neck restraints are HIGHLY recommended
10. Fire Extinguisher that is securely mounted in reach of driver required
11. Battery must be in an enclosed box, securely mounted. Battery may be moved into cab area, covered and securely fastened. Must have a battery shutoff switch that is accessible.
12. All Driveshafts and lead must be painted white & car # must be written on them

CAR BUILD

1. **Must be a rear wheel drive V8**
2. **Tires/Rims:**
 - a. 400+ Treadwear, 70 Series, DOT ONLY
(EX: P235/70R15 or P225/70R15)
 - b. *Tire size must be highlighted or marked for quick inspection!*
 - c. Rims: 7" or 8"

3. **Spoilers:**
 - a. Rear mounted spoilers are allowed
 - b. MAXIMUM height is 44" from ground to top of spoiler
 - c. MAXIMUM 5" x 60" wide of a single piece of clear lexan
 - d. End of spoilers may not be boxed; no forward mounting brackets
 - e. NO SIDE PANELS
4. **Weight:**
 - a. 3150 lbs
 - b. 55.00% or less on left side
5. **Frames** must be a STOCK CHASSIS- NO TUBE CHASSIS ALLOWED. Track officials have final approval.
6. **Carburetors** must be a 4412
7. **Shocks** must be no more than \$150 MSRP
8. **Transponder** is to be mounted 12" behind center of rear axle

2-Way Radios or mirrors of any kind, including spot mirrors, are NOT ALLOWED!

These rules are subject to change at the discretion of tech. Please reach out to Star Tech for any related questions.