

STAR SPEEDWAY STREET STOCK RULES 2023

RIMS: 7" or 8"

TIRES – Hoosier 790 will be only tire allowed. A inventory TBD will established at a later date.

TREAD WIDTH: Maximum of 73" measured from outside lip to outside lip.

RIDE HEIGHT: Chassis height 5", body height 3" with driver in car.

REAR SPOILER: 5" x 60", must be see thru, no forward facing spoiler braces.

CLUTCH: Only stock appearing, 10 ½" flywheel and pressure plate, No multiple disc, No aluminum components.

LEFT SIDE WEIGHT: Max. 55% AFTER the race.

SHOCKS/STRUTS/COIL OVERS: \$150 MSRP maximum. All shocks must have part #'s on them to verify cost. Gen 3 and Gen 4 struts or coilovers Maximum MSRP \$180.

BODIES: Street stock type only. No ABC Late Model bodies, No wedge bodies, rear bumper cover needs to extend to rear bumper mount. Rear of car MUST be enclosed.

BUILT ENGINE: 3100 LBS

602 CRATE ENGINE: 3000 LBS * Crate engine must be SEALED

All weights will be checked after race.

TRANSMISSION: Stock style transmission only.

HEADERS: Down under Street Stock type headers ONLY. Must run track approved mufflers.

CHASSIS: Perimeter style only. No straight rail. 3 links are allowed on metric cars, must be solid mount and NO rubber components. Stock mount steering box only. No steering racks allowed unless the car came factory with a steering rack. Only stock type lowers and spindles allowed. Driveshaft must have 2 loops, MANDATORY. Hamm, Johnson and Lefthander clips, part #001358207 are legal. NO underslung Late Model style rear clips allowed.

WHEEL BASE: Gen 2 Camaro and Metric – 108", +/- 1", Gen 3 / 4 Camaro – 101", +/- 1"

BRAKES: Stock mount brakes

SWAY BARS: Stock type, stock mount only. NO 3 piece bars allowed.

ENGINE RULES:

BUILT ENGINES – 460 Max Lift measured at the valve, cast iron heads and blocks only. No aluminum, intake Edelbrock 2101 & 2116

ENGINE LOCATION – stock mounting points, no motor plates

IGNITION – Stock style HEI ignition ONLY. No MSD, NO external rev limiting devices.

CARB SPACER – Maximum of one, 1" spacer. Single gasket on top and bottom.

CARBURETOR – Built and Non-Sealed Crates, 500 CFM 4412, 3100 lbs. Sealed 602 crate, 4BBI 650 CFM, 3000 lbs or 4412 2 BBL 500 CFM, 2950 lbs. All carbs must pass GO-NO GO tools.

FUEL CELLS – Must be centered in frame rails. Minimum height is 8".

FUEL – Will be subject to tech. No additives or oxygenators allowed.

RADIOS / MIRRORS : NO radios, NO mirrors allowed.

TRANSPONDERS: Are mandatory and must be mounted on rightside frame rail, 12" back from center of rear axle.

RACEIVERS – Are mandatory. Failure to do so may result in car starting rear.

STAR LICENSE – All drivers competing in 2023 that are in points must have a valid 2023 Star license.

These rules are subject to change at the discretion of tech. Tech questions contact TJ Laro @ 978-284-0606