

## **STREET STOCK PRE-HOWLER '22 RULES**

**RIMS** – 7" or 8" rims

**TIRES** – Must run 8" Hoosier 790s. Maximum 2 new tires bought at Star Speedway.

**RIDE HEIGHT** – 5" minimum ride height with driver in car.

**SPOILER** – Maximum height of spoiler is 5" and 60"

**WEIGHT** – Maximum left side weight is 55%

**SHOCKS** – Maximum \$150 MSRP

**FUEL** – No additives or oxygenators. Samples will be taken after the race. Sunoco 110 is available for sale at the racetrack.

**RADIOS** – NO radios allowed. All drivers must have one way communication to race control.

**TRANSPONDERS** – All cars must have working transponder located 10 – 12" back from center of rear axle, mounted on frame rail pointing down towards track. We have a limited number available for rent.

**BODIES** – NO ABC Late Model, Late Model or Wedge type bodies allowed.

**ENGINES** – Cast iron steel heads only. Must use Edelbrock 2101 or 2116 intake. Max. lift for camshaft measured at the valve is .460.

**CARB** – If not a sealed crate 602 then must use Holley 4412 500 CFM. Sealed crate 602 may use Holley 650 CFM. Maximum 1" spacer between carb and intake.

**CHASSIS** – Only stock mount steering boxes allowed, no rack & pinion steering unless stock from factory, (i.e. 4<sup>th</sup> Gen Camaro). Only stock type lower control arms and spindles allowed.

**SWAY BARS** – Only stock type allowed in stock mount location, no 3 piece allowed.

**TREAD WIDTH** – 73" measured outside lip to outside lip

**WEIGHTS** –

Built engine with Holley 4412 2 Barrel 500 CFM – 3100

602 Sealed crate with Holley 4412 2 Barrel 500 CFM – 2950

602 Sealed crate with Holley 650 CFM 4 Barrel – 3000

FLYING TIGERS – 3000, must meet all Flying Tiger rules